

A person with short brown hair, wearing a blue jacket, is seen from the side, aiming a rifle. The rifle has a blue and black scope. In the background, there is a brick building and a target with a bullseye. The scene is outdoors with green foliage.

AIRCARTRIDGE TECHNOLOGY

By

Dick Pepper (SDE)

Henk Holsboer (AMI)


Report Documentation Page

Report Date 13Aug2001	Report Type N/A	Dates Covered (from... to) -
Title and Subtitle Aircartridge Technology	Contract Number	
	Grant Number	
	Program Element Number	
Author(s) Pepper, Dick; Holsboer, Henk	Project Number	
	Task Number	
	Work Unit Number	
Performing Organization Name(s) and Address(es) SDE	Performing Organization Report Number	
Sponsoring/Monitoring Agency Name(s) and Address(es) NDIA (National Defense Industrial Association) 211 Wilson Blvd, STE. 400 Arlington, VA 22201-3061	Sponsor/Monitor's Acronym(s)	
	Sponsor/Monitor's Report Number(s)	
Distribution/Availability Statement Approved for public release, distribution unlimited		
Supplementary Notes Proceedings from the 2001 Joint Services Small Arms Symposium, Exhibition & Firing Demonstration 13-16 August 2001 Sponsored by NDIA, The original document contains color images.		
Abstract		
Subject Terms		
Report Classification unclassified	Classification of this page unclassified	
Classification of Abstract unclassified	Limitation of Abstract UU	
Number of Pages 20		

- Who are we & where are we based?
- Airmunition concept.
- Product range & benefits.
- Energy comparison.
- AirCartridge technology & kinematic model.
 - Methodology.
 - Trials.
 - Results & Validation.
- System Modelling.
- Conclusions.

Organisation

SDE



Mission



To provide **safe, realistic & cost effective** weapon training systems, using the patented concept of compressed air as an energy source.



The Concept

SDE



Small Calibre

SDE



Product Range

SDE



Benefits



- **Cost Effective**
 - Each cartridge can be reloaded in excess of 500/2000 times.
- **Environmentally Friendly**
 - Uses only air.
 - Can be used indoors without a need for ventilation.
- **Safe**
 - No energetic materials are used.
 - Patented vent hole in the side of the chamber.
- **Reliable**
- **Variable Velocity**
 - For special applications, the muzzle velocity can be varied by varying the pressure.

Energy Comparison

9mm

SDE

	Pyrotechnic Cartridge	AirCartridge
Maximum Pressure	3200 (bar) 46,400 (psi)	250 (bar) 3,625 (psi)
Total Energy (J)	1840	9
Muzzle Energy (J)	580	2.5

AirCartridge Technology

Objectives

SDE

- To allow a wider application of the technology.
- To assist production by identifying critical areas of the design.
- To reduce development time and cost of future products.

- Produce a Kinematic Model of the AirCartridge.
- Conduct laboratory tests, to obtain pressure & time data within the AirCartridge, using both standard & non-standard components.
- Produce algorithms to predict the flow of air through the valves.
- Insert the data into the Kinematic Model.
- Validate the model.

Trial Programme




- **Build Standard Variations**
 - Piston (main) valve travel.
 - Flow restriction from main to rear chamber.


- **Initial Charge Pressure**
 - Pressures at 200 bar (2900 psi) & 100 bar (1450 psi).

- **Trials**
 - Determination of Spool Valve activation energy.
 - Record pressure/time data.

Trial Results




Air Flow Algorithms




Model Results

Chamber Pressures

Prear P_{main} vs. t (ms)



Model Results




System Modeling

SDE



System Modeling



Model Conclusions



- A Kinematic Model has been developed which accurately represents the action of the AirCartridge, which allows us to:
 - Identify & quantify critical design features.
 - Develop new products more efficiently.
- This model can be extended to include the complete weapon system, further reducing development time and costs.

QUESTIONS?

SDE

